



Indurabond

ALUMINIUM COMPOSITE PANELS

Tophat Fixing System


Version 2.5
January 2025

CONTENTS


1. Components	4
2. Vertical Panel Joint	5
3. Horizontal Panel Joint	6
4. Inter-storey Joint	7
5. Internal Corner Panel	8
6. External Corner Panel	9
7. Wall To Soffit - A	10
8. Wall To Soffit - B	11
9. Base Detail - A	12
10. Base Detail - B	13
11. Base Detail - C	14
12. Precast Wall - A	15
13. Precast Wall - B	16
14. Precast Wall - C	17
15. Fibre Cement Internal Corner - A	18
16. Fibre Cement Internal Corner - B	19
17. Vertical Profiled Cladding Internal Corner	20
18. Horizontal Profiled Cladding Internal Corner	21
19. Pipe Penetration @ Soft	22
20. Vertical Profiled Metal Junction	23
21. Parapet Option - A	24
22. Parapet Option - B	25
23. Parapet Option - C	26
24. Parapet Option - D (w/ minimal upstand)	27

CONTENTS


25. Parapet Top Joint	-----	28
26. Fascia To Soffit - A	-----	29
27. Fascia To Soffit - B	-----	30
28. Fascia To Soffit - C	-----	31
29. Fascia To Soffit - D	-----	32
30. Fascia To Soffit - E	-----	33
31. Eyebrow Sill Detail	-----	34
32. Typical Upstand Detail	-----	35
33. Typical Commercial Window Head	-----	36
34. Typical Commercial Window Sill	-----	37
35. Typical Commercial Window Jamb - A	-----	38
36. Typical Commercial Window Jamb - B	-----	39
37. Typical Residential Window Head	-----	40
38. Typical Residential Window Sill	-----	41
39. Typical Residential Window Jamb - A	-----	42
40. Typical Residential Window Jamb - B	-----	43
41. Wall Box Penetration Detail	-----	44
42. Wall Pipe Penetration Detail	-----	45
43. Fin Mounting Detail	-----	46
44. General Differential Movement	-----	47
45. Meter Box Penetration	-----	48
46. Aluminium Stiffener To Indurabond	-----	49



Indurafix High Z-Angle (First Fix)
Alloy & Temper: 6060-T6
Colour: Mill Finish



Indurafix Low Z-Angle (Second Fix)
Alloy & Temper: 6060-T6
Colour: Mill Finish




RHS Stiffener 50X25X2mm
Alloy & Temper: 6060-T6
Colour: Mill Finish
Adhesive Glue: Minimum 2mm thick & minimum 50mm wide strip of Sabrebond SMP60
Alignment: Stiffener to be parallel to short edge

Fixing Requirement of First & Second Fix Z-Angle to Top Hat

Proposed Fastener Diameter: 4.88MM Screw
Minimum Aluminium Edge Distance: 7.32MM

For more information refer to the *INDURABOND Aluminium Laminated Panels (Top Hat) Engineering Judgement*




16mm TOP HAT EXTRUSION
Alloy & Temper: 6060-T6
Colour: Mill Finish

Fixing Requirements

- 1. Top Hat to Timber Substrate**
Proposed Fastener Diameter: 4.88mmØ
No. of Fastener: 2
Minimum Timber Embedment Depth: 40mm
Minimum Aluminium Edge Distance: 10mm
Minimum Timber Edge Distance: 20mm
- 2. TopHat to Steel Stud Substrate**
Proposed Fastener Diameter: 5.59mm
No. of Fastener: 2
Minimum Aluminium Edge Distance: 12mm
Minimum Steel Edge Distance: 12mm
- 3. TopHat to Concrete Substrate**
Proposed Fastener: M6 Hilti HUS4-HR or M6 Anzor AnchorMark G316SS
No. of Fastener: 2
Minimum Concrete Embedment: 55mm
Minimum Concrete Edge Distance: 50mm
Minimum Aluminium Edge Distance: 12mm


For stiffener spacings refer to the *Indurabond Aluminium Composite Panels (Z-Angle Fixing System) Engineering Judgement & for more information refer to Induracore Aluminium Laminated Panels (Z-Angle on Top Hat Fixing System).*
Structure shown on the typical details are on timber framing. Fixing system can also be applied on steel framing.




25mm TOP HAT EXTRUSION
Alloy & Temper: 6060-T6
Colour: Mill Finish


Fire Cavity Barrier (By Others)

- Ryanfire Intuspan Fire Cavity Barrier or equivalent, where required, to be installed in accordance with C/AS2




Indurabase Extrusion
Alloy & Temper: 6060-T6
Colour: Mill Finish








4. INTER-STOREY JOINT (SECTION DETAIL)


Drawing Scale 1:2





























































IMPORTANT NOTES:


- A. PARAPET DETAIL OPTION IS NOT SUITABLE FOR ABSEILING LOAD.
- B. FOR LOW ROOF UPSTAND ONLY.
- C. THIS DETAIL DOES NOT COMPLY WITH THE BUILDING CODE REQUIREMENTS BUT MAY BE CONSIDERED AN ACCEPTABLE ALTERNATIVE SOLUTION.
- D. IT IS THE RESPONSIBILITY OF THE BUILDER OR ARCHITECT TO ENSURE THAT THIS DETAIL IS SATISFACTORY. SPECIFIC INSTRUCTIONS ARE REQUIRED FOR ITS IMPLEMENTATION.






IMPORTANT NOTES:


- RECOMMENDED TO HAVE THE PANEL BOTTOM SLOPING @1.5° TOWARDS THE SIDE WHERE THE DRAIN HOLE IS LOCATED TO AVOID RISK OF PONDING.






IMPORTANT NOTES:

- RECOMMENDED TO HAVE THE PANEL BOTTOM SLOPING @1.5° TOWARDS THE SIDE WHERE THE DRAIN HOLE IS LOCATED TO AVOID RISK OF PONDING.




IMPORTANT NOTES:

- RECOMMENDED TO HAVE THE PANEL BOTTOM SLOPING @1.5° TOWARDS THE SIDE WHERE THE DRAIN HOLE IS LOCATED TO AVOID RISK OF PONDING.





IMPORTANT NOTES:


- RECOMMENDED TO HAVE THE PANEL BOTTOM SLOPING @1.5° TOWARDS THE SIDE WHERE THE DRAIN HOLE IS LOCATED TO AVOID RISK OF PONDING.





IMPORTANT NOTES:
 - RECOMMENDED TO HAVE THE PANEL BOTTOM SLOPING @1.5° TOWARDS THE SIDE WHERE THE DRAIN HOLE IS LOCATED TO AVOID RISK OF PONDING.











































Auckland Office
5 Piermark Drive
Rosedale
Auckland 0632
0508 726 358

Head Office
10 Mako Street,
Dargaville
09 439 4357

info@paneltec.co.nz
www.paneltec.co.nz

